

Tripp Lite ECO550UPS uninterruptible power supply (UPS) Standby (Offline) 0.55 kVA 300 W 10 AC outlet(s)

Brand : Tripp Lite

Product code: ECO550UPS

Product name : ECO550UPS



Tripp Lite ECO550UPS. UPS topology: Standby (Offline), Output power capacity: 0.55 kVA, Output power: 300 W. AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, AC outlets quantity: 10 AC outlet(s). Battery voltage: 12 V, Typical backup time at full load: 1.2 min, Typical backup time at half load: 5 min. Form factor: Tower, Product colour: Black, Housing material: Acrylonitrile butadiene styrene (ABS). Width: 110 mm, Depth: 184.9 mm, Height: 104.9 mm



Features		Design	
UPS topology *	Standby (Offline)	Form factor *	Tower
Output power capacity *	0.55 kVA	Housing material	Acrylonitrile butadiene styrene (ABS)
Output power *	300 W	Cable length	1.5 m
Waveform *	Pure sine	Product colour *	Black
Input operation voltage (min) *	110 V	LED indicators	✓
Input operation voltage (max) *	120 V	Certification	UL1778, CSA, NOM, FCC
Input frequency *	60 Hz	Operational conditions	
Output operation voltage (min)	115 V	Operating temperature (T-T)	0 - 40 °C
Output operation voltage (max)	120 V	Storage temperature (T-T)	-15 - 45 °C
Output frequency	50/60 Hz	Operating relative humidity (H-H)	0 - 90%
Maximum current	15 A	Operating altitude	0 - 3048 m
Surge energy rating	316 J	Technical details	
Number of input phases	1	Compliance certificates	RoHS
EMI/RFI noise filtering	✓	Weight & dimensions	
Surge protection	✓	Width	110 mm
Surge protection features	Telephone	Depth	184.9 mm
Audible alarm(s)	✓	Height	104.9 mm
Country of origin	Vietnam	Weight	1.8 kg
Ports & interfaces		Package width	144 mm
AC outlet types	NEMA 5-15R	Package depth	275.8 mm
Power plug	NEMA 5-15P	Package height	186.9 mm
AC outlets quantity	10 AC outlet(s)	Package weight	2.36 kg
USB port	✓	Packaging data	
USB 2.0 ports quantity	1	Cables included	USB cable
Modem (RJ-11) ports	1	Manual	✓
Ethernet LAN (RJ-45) ports	1		
Battery			
Battery voltage	12 V		

Battery		Logistics data	
Typical backup time at full load	1.2 min	Master (outer) case width	286 mm
Typical backup time at half load	5 min	Master (outer) case length	591.8 mm
Cold start	✓	Master (outer) case height	394 mm
		Master (outer) case gross weight	16.7 kg
		Products per master (outer) case	8 pc(s)
		Master (outer) case GTIN (EAN/UPC)	10037332211061



0037332211064



037332211064

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.