



APC SRT6KXLT uninterruptible power supply (UPS) Double-conversion (Online) 6 kVA 6000 W 6 AC outlet(s)

Brand : APC

Product code: SRT6KXLT

Product name : SRT6KXLT

6000W/6000VA, 208V, 2PH + G, 2x NEMA L6-20R, 3x NEMA L6-30R, Black

APC SRT6KXLT uninterruptible power supply (UPS) Double-conversion (Online) 6 kVA 6000 W 6 AC outlet(s):

APC Smart-UPS On-Line,6000 Watts /6000 VA,Input 208V /Output 208V, Extended runtime model

Includes: CD with software, Documentation CD, Installation guide, Removable support feet, Temperature Probe, USB cable, User Manual, Warranty card, Web/SNMP Management Card
APC SRT6KXLT. UPS topology: Double-conversion (Online), Output power capacity: 6 kVA, Output power: 6000 W. AC outlet types: NEMA L6-20R, NEMA L6-30R, AC outlets quantity: 6 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery recharge time: 1.50 h. Form factor: Compact, Product colour: Black, Display type: LCD. Width: 174 mm, Depth: 719 mm, Height: 432 mm



Features		Design	
UPS topology *	Double-conversion (Online)	Product colour *	Black
Output power capacity *	6 kVA	Display type	LCD
Output power *	6000 W	LED indicators	✓
Waveform *	Sine	International Protection (IP) code	IP20
Input operation voltage (min) *	100 V	Certification	CSA, FCC, NOM, UL
Input operation voltage (max) *	275 V	Operational conditions	
Input frequency *	40/70 Hz	Operating temperature (T-T)	0 - 40 °C
Output operation voltage (max)	240 V	Storage temperature (T-T)	-15 - 45 °C
Output frequency	50/60 Hz	Operating relative humidity (H-H)	0 - 95%
Surge energy rating	480 J	Storage relative humidity (H-H)	0 - 95%
Crest factor	3:1	Operating altitude	0 - 3000 m
Emergency Power Off (EPO)	✓	Non-operating altitude	0 - 15000 m
Output voltage Total Harmonic Distortion (THD)	3%	Technical details	
Ports & interfaces		Sustainability certificates	ENERGY STAR
AC outlet types	NEMA L6-20R, NEMA L6-30R	Compliance certificates	RoHS
AC outlets quantity	6 AC outlet(s)	Weight & dimensions	
USB 2.0 ports quantity	1	Width	174 mm
Serial ports quantity	1	Depth	719 mm
Ethernet LAN (RJ-45) ports	1	Height	432 mm
Battery		Weight	61.2 kg
Battery technology	Sealed Lead Acid (VRLA)	Package width	610 mm
Battery recharge time	1.50 h	Package depth	960 mm
Design		Package height	370 mm
Form factor *	Compact	Package weight	64.4 kg

Logistics data

Products per pallet

6 pc(s)



0045986092731



045986092731



0731304301677



731304301677

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.