

## Tripp Lite SmartPro LCD 120V 1500VA 900W Line-Interactive UPS, Tower, LCD Display, USB

**Brand :** Tripp Lite

**Product code:** SMART1500LCDT

**Product name :** SmartPro LCD 120V 1500VA 900W Line-Interactive UPS, Tower, LCD Display, USB

SmartPro, 900W, 1500VA, 120V AC, 50/60Hz, 20A, LCD, 650J  
Tripp Lite SmartPro LCD 120V 1500VA 900W Line-Interactive UPS, Tower, LCD Display, USB. UPS topology: Line-Interactive, Output power capacity: 1.5 kVA, Output power: 900 W. AC outlet types: NEMA 5-15R, Power plug: NEMA 1-15P, AC outlets quantity: 10 AC outlet(s). Typical backup time at full load: 1.6 min, Typical backup time at half load: 10 min, Battery recharge time: 8 h. Form factor: Tower, Product colour: Black, Cable length: 1.8 m. Width: 146.1 mm, Depth: 396.2 mm, Height: 203.2 mm



Features		Battery	
UPS topology *	Line-Interactive	Battery recharge time	8 h
Output power capacity *	1.5 kVA	<b>Design</b>	
Output power *	900 W	Form factor *	Tower
Input operation voltage (min) *	120 V	Cable length	1.8 m
Input operation voltage (max) *	120 V	Cooling type	Active
Input frequency *	50/60 Hz	Product colour *	Black
Output operation voltage (min)	120 V	Display type	LCD
Output operation voltage (max)	24 V	Certification	UL1778, CSA, NOM, FCC-15 A (EMI)
Surge energy rating	650 J	<b>Operational conditions</b>	
Response time	2 ms	Operating temperature (T-T)	0 - 40 °C
Efficiency	95%	Storage temperature (T-T)	-15 - 50 °C
EMI/RFI noise filtering	✓	Operating relative humidity (H-H)	0 - 95%
Surge protection	✓	<b>Weight &amp; dimensions</b>	
Surge protection features	Coax, Network	Width	146.1 mm
Power protection features	Over voltage, Under voltage	Depth	396.2 mm
Country of origin	Vietnam	Height	203.2 mm
<b>Ports &amp; interfaces</b>		Weight	11.5 kg
AC outlet types	NEMA 5-15R	Package width	228.6 mm
Power plug	NEMA 1-15P	Package depth	490.2 mm
AC outlets quantity	10 AC outlet(s)	Package height	281.9 mm
USB 2.0 ports quantity	1	Package weight	12.7 kg
Serial ports quantity	1	<b>Logistics data</b>	
<b>Battery</b>		Master (outer) case width	228.6 mm
Typical backup time at full load	1.6 min	Master (outer) case length	490.2 mm
Typical backup time at half load	10 min	Master (outer) case height	281.9 mm
		Master (outer) case gross weight	12.7 kg
		Products per master (outer) case	1 pc(s)

**Logistics data**

Master (outer) case GTIN (EAN/UPC) 00037332174109



0037332174109



037332174109

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.